

RIDGE TAPE DKA VENT

PRODUCT:

Steam permeable ridge tape that consists from two aluminum stripes with self adhesive stripes from the bottom side, joined together with geotextile.

PROPERTIES:

- Effective ridge ventilation and corners of roof with the use of steam permeable geotextile
- The tape lets the water steam and air in, and at the same time protects against getting rain water, snow and insects underneath the roof
- High resistance to weather conditions and UV radiation
- unusually firm joining of geotextile with aluminum
- Very high flexibility enables simple installation
- Various tape widths enable the right selection of the tape to a specific roof sheeting and the roof shape

THE USAGE:

- Ventilation and tightening ridge on slant roofs covered with tiles and steel tile-sheets
- The tape enables getting rid of water steam leaking through the layers of roof construction of the used attic and at the same time protects against getting water, dust under the roof

SPECIFICATION:

ITB Technical approval number: ITB-KOT-2020/1225 wyd. 1

Material	Aluminum + Geotextile
Aluminum thickness	0,10mm - 0,12 mm
Geotextile colour	black
Ventilation surface	app. 170 cm ² /1 linear m.
Geotextile weight	app. 100g/m ²
Fire resistance classification	B2
Temperature resistance	-30 to + 80°C
Treating temperature	+ 5 to + 40°C

ROLL SIZE

390mm, 340mm, 310mm, 300 mm, 230mm, 200mm, 180mm, 150mm

Roll length: 5m

Packing: cardboard box

ALUMINUM COLOURS

anthracite, brick-red, brown 8017, brown 8019, black, green, cherry-red, auburn

STORING

12 months from the production date in intact original boxes, in cold and dry place in the temperature of 10 °C

HEALTH AND SAFETY RECCOMENDATION

While working with ridge tape, only ordinary rules of work hygiene needed.